



Series:
Sentry Wall Pack (SWP)

Fixture Type :
Large Deep Full Cutoff Wall Pack

Project Name	Fixture Type	Catalog #	Quantity
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>



Design Features / Specifications

HOUSING:

Die Cast Aluminum Housing & Hinged Full Cutoff Front Frame, 1/2" Coin Plugs with O-rings for Conduit & Photocell, Textured Architectural Bronze Powdercoat Finish Over a Chromate Conversion Coating

MOUNTING:

Cast-in Template for Mounting Directly Over a 4" Recessed Outlet Box, or Use 1/2" Surface Conduit.

LG LED MODULE:

Luminous Flux: See Chart
CRI: 80+, CCT: 4000K, 5700K or 6500K
Operating Temperature: -40 ≈ 50°C
50,000 Hours
Module has IP67 Rating
RoHS Compliant
R9: -0.9

WATTAGE:

LED: 6 x 9w or 12w

DRIVER:

Electronic Driver, 120-277V, 50/60Hz
Power Factor: .90
Input Current: 0.9A@120VAC
Current: 530mA
THD: ≤20%
System Wattage: 13.6w per Module

LISTINGS & RATINGS:

CSA: Listed for Wet Locations
Meets Dark Sky Requirements
LM-79 Report Available on Select Models

OPTIONS:

Dimmable Driver
2.5KV Surge Protection
Custom Colors Available Upon Request.

TOTAL LUMINOUS FLUX PER MODULE	CCT	Optic Type	
		9w	12w
	4000K	726	1100
	5700K	888	1345
	6500K	888	1345

*Options	Description
HB350W-L3	Wattstopper Passive Infrared Occupancy Sensor, Wet Location, 360° Lens, 40" Diameter Coverage From 20' Height, 120/277V
HB350W-L4	Wattstopper Passive Infrared Occupancy Sensor, Wet Location, 360° Lens, 60" Diameter Coverage From 40' Height, 120/277V

Note: RENOVA products are constantly being improved; therefore, the information shown is subject to change without notice. Always consult your lighting representative or RENOVA Lighting Systems, Inc. for the latest information.

Sentry Large Deep Full Cutoff Wall Pack

Catalog # Description

Complete Units


Ordering Information

Example: SWP-L-L-F-6X9-UNV-40K-BRZ

SWP-L	Fixture Series:	SWP-L = Sentry Wall Pack - Large Deep Full Cutoff Wall Pack
L	Light Source:	L = Light Emitting Diode (LED)
F	Optics	F = Medium Beam Spread
6X	Number of LED Arrays:	6X = Six
	Wattage:	9 = 9w (LED) 12 = 12w (LED)
UNV	Driver	UNV=Universal Voltage (120v-277v)
	Color Temperature:	40K = 4000K 57K = 5700K 65K = 6500K
	Color	BRZ=Bronze (Standard) CLR=Custom Color (Specify)
	Mounting	N/A
	Options*	(Blank) = None L3 = HB350W-L3 Wattstopper Occupancy Sensor, 20' Height L4 = HB350W-L4 Wattstopper Occupancy Sensor, 40' Height SF = Single Fuse DF=Double Fuse SP = Surge Protection

*Contact Factory for all Other Options

Dimensional Information



Photometric Information

