



Series: **Compact Wet Location LED Exit Sign (CWL)** Fixture Type: **Die-Cast Aluminum (Wet Location)**

Project Name	Fixture Type	Catalog #	Quantity
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>



Design Features / Specifications

ILLUMINATION

Ultra bright, energy efficient, long life Red or Green LED.

ELECTRICAL

Dual 120/277 voltage.

Unique bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check battery).

4.8V long life, maintenance-free, rechargeable NiCd battery.

Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.

Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

Polycarbonate mounting canopy included for top or end mount.

Universal K/O pattern on back plate for wall mount.

HOUSING

5VA flame retardant, UV-stabilized polycarbonate in white, black or gray finish.

High-impact resistant, UV-stabilized polycarbonate clear lens.

Corrosion-resistant enclosure with engineering grade silicone gasket.

Top and side K/O's provided for conduit feed applications.

EZ snap-out chevron directional indicators.

OPTIONS

SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and life safety codes.

2C: Dual circuit option on the AC-only unit enables it to be connected to two different (one acting as a back-up to the other) supplies at the same time.

TP: Tamper-proof hardware helps prevent unauthorized access to the unit.

Custom: Signs available with requested "special" wording.

WARRANTY / LISTING

Five year warranty on all electronics and housing. Battery pro rated for five years.

Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.


UL Listed for wet locations (-20°C – 50°C).

CWL Series Die-Cast Aluminum LED Exit Sign (Wet Location)

Catalog #	Description
Complete Units	
Ordering Information	
Example: CWL-2-R-G-EM-SDT	
<input type="text"/>	Model: CWL = CWL LED Exit Sign (Compact Wet Location)
<input type="text"/>	# of Faces: 1 = Single Face 2 = Double Face
<input type="text"/>	Letter Color: R = Red G = Green
<input type="text"/>	Housing Color: W = White (with white faceplate) B = Black (with black faceplate) G = Gray (with white faceplate)
<input type="text"/>	Battery: (Blank) = AC-Only EM = Battery Back-up
<input type="text"/>	Options: SDT = Self-diagnostics ¹ 2C = Dual Circuit Operation ² TP = Tamper-Proof Custom = Custom Wording

¹Available only with EM units ²Available only with AC units

Dimensional Information



Electrical Information

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)	
	120v	277v	120v	277v
CWL-2-R/G-**-**	2.7	2.7	0.025	0.011
CWL-2-R/G-**-EM-SDT	3.3	3.4	0.030	0.014
CWL-2-R/G-**-**2C	2.4	2.4	0.023	0.011

Note: RENOVA products are constantly being improved; therefore, the information shown is subject to change without notice. Always consult your lighting representative or RENOVA Lighting Systems, Inc. for the latest information.