



Series: Die-Cast Standard LED Exit Sign (DCS) Fixture Type: Die-Cast Aluminum

Project Name	Fixture Type	Catalog #	Quantity
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>



Design Features / Specifications

ILLUMINATION

Ultra bright, energy efficient, long life Red or Green LED.

ELECTRICAL

Dual 120/277 voltage.
 Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
 4.8V long life, maintenance-free, rechargeable NiCd battery.
 Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
 Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

Aluminum mounting canopy included for top or end mount.
 Universal K/O pattern on back plate for wall mount.

HOUSING

Premium-grade, aluminum housing (also available in black or white powder-coated finishes).
 Field selectable knockout chevron directional indicators.
 Unique design allows double face conversion in the field.
 Quick-snap face plate closure.

OPTIONS

TP: Tamper-proof hardware helps prevent unauthorized access to the unit.
 SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and life safety codes.
 2C: Dual circuit option on the AC-only unit enables it to be connected to two different (one acting as a back-up to the other) supplies at the same time.
 USA: Substantial transformation assembly in the U.S. complies with "Assembled in the USA" under the Buy American Act.

WARRANTY / LISTING


Five year warranty on all electronics and housing. Battery pro rated for five years.
 Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
 UL Listed for damp locations (0°C – 50°C).

DCS Series Die-Cast Aluminum LED Exit Sign (Standard)

Catalog #	Description
Complete Units	
Ordering Information	
Example: DCS-2-R-B-A-EM-SDT	
<input type="text" value="DCS"/>	Model: DCS = DCS LED Exit Sign (Die-Cast Standard)
<input type="text"/>	# of Faces: 1 = Single Face 2 = Double Face 3 = Universal Single/Double Face
<input type="text"/>	Letter Color: R = Red G = Green
<input type="text"/>	Housing Color: W = White B = Black A = Aluminum
<input type="text"/>	Face Plate Color: W = White B = Black A = Aluminum
<input type="text"/>	Battery: (Blank) = AC-Only EM = Battery Back-up
<input type="text"/>	Options: SDT = Self-diagnostics ¹ 2C = Dual Circuit Operation ² TP = Tamper-Proof USA = Assembled in USA

¹Available only with EM units ²Available only with AC units

Dimensional Information



Electrical Information

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)	
	120v	277v	120v	277v
DCS-2-R-**-EM-2C-SDT	3.2	3.6	0.031	0.019
DCS-2-G-**-EM-2C-SDT	3.8	4.4	0.033	0.017

Note: RENOVA products are constantly being improved; therefore, the information shown is subject to change without notice. Always consult your lighting representative or RENOVA Lighting Systems, Inc. for the latest information.