

The Semi-Recessed Wrap (SRW) Fixture family has been developed to dramatically improve energy efficiency and quality of light using Solid State Lighting (SSL) technologies. The Semi-Recessed Wrap Series provides an attractive, low profile, energy efficient architectural look which has been specifically designed to replace existing fluorescent lighting or for use in new construction. Comfortable, low glare, uniform lighting is attributed to this style of fixture. Typical applications for this type of product are interior spaces where finished ceilings and walls exist. Applications include:

- Commercial/Corporate Office Spaces
- Schools, Colleges and Universities
- Retail Spaces, Public Spaces and Airports
- Hospitals, Government Facilities and Military Bases



DLC Application Category #7
"Linear Ambient Lighting
of Interior Commercial Spaces"

DesignLights Consortium® (DLC) qualified product. Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at www.designlights.org to confirm which versions are qualified

project:

fixture type:

catalog #:

quantity:



ORDERING GUIDE

SRW										
PREFIX/SERIES	SIZE	OPTICS (DISTRIBUTION)	LUMEN OUTPUT*	DRIVER VOLTAGE	DRIVER TYPE	COLOR TEMP.	CRI	LENS (DIFFUSER)	HOUSING COLOR / FINISH	FIXTURE OPTIONS
SRW - Semi-Recessed Wrap Fixture	1 - 1' 2 - 2' 3 - 3' 4 - 4' 6 - 6' 8 - 8'	N - Normal C - Custom (Specify)	L010 10W 67W L020 15W 74W L030 22W 82W L040 30W 89W L050 37W 96W L060 44W 103W L070 51W 110W L080 59W 117W	UNV - Universal Voltage (120v - 277v) (60 Hz) (Standard) 120 - 120v, 60Hz 277 - 277v, 60Hz 347 - 347v *Special Order Only	DM - 0-10v Low Voltage Dimming (10% - 100%) (Standard) SD - Step Dimming (50% / 100%) LV - Line Voltage Dimming *Specify Voltage (120v or 277v)	C27 - 2700 K* C30 - 3000 K* C35 - 3500 K C40 - 4000 K C50 - 5000 K* *Special Order Only	Blank - 80 CRI 9 - 90 CRI* S - Sunlike 95 CRI* *Special Order Only	AF - Frosted Linear Prism Acrylic Lens (Optional) CS - Custom (Specify)	PP - Pre-painted (White) (Standard With Pop Rivet Construction) GW - Gloss White (Smooth) TW - Textured White TB - Textured Black CS - Custom Finish (Specify)	SNS21x - Philips Wireless Sensor (EasySense) ††† SVP - Silvacir PIR Wireless Sensor ††† SVM - Silvacir Microwave Sensor ††††† LAR - Lutron Athena Wireless control RF Only ††††† LAP - Lutron Athena Wireless PIR Sensor ††† LVR - Lutron Vive Wireless control RF Only ††††† LVP - Lutron Vive Wireless PIR Sensor ††† WLI - Wave Linx Integral PIR Sensor ††† Axx - Auxiliary output 12 or 24V EM - Emergency Battery Pack †

*L(x) = Delivered Lumens
Example: L090 = 9,000 Lumens

277v) 24'-0"

*EXAMPLE: CONTINUOUS ROW @ 1000 LUMENS PER FOOT

(QTY=1) SRW8-N-L080-UNV-DM-C40-AF-PP
(QTY=1) SRW6-N-L060-UNV-DM-C40-AF-PP

(QTY=1) SRW4-N-L040-UNV-DM-C40-AF-PP
(QTY=1) SRW3-N-L030-UNV-DM-C40-AF-PP

(QTY=1) SRW2-N-L020-UNV-DM-C40-AF-PP
(QTY=1) SRW1-N-L010-UNV-DM-C40-AF-PP








RENOVA Products Listed on the DLC Qualified Product List (QPL) See page 4 for complete list.

† Standard "EM" option to be NiCd Battery @ 5 Watts constant power @ 90 min. duration (standard). Consult factory for all available options.
 † † † PIR sensors provide: Occupancy/Vacancy, Daylight Harvesting, Task Tuning & Advanced Grouping control options. (max 12 ft mounting height, highbay options available upon request)
 † † † Microwave sensor provides: Occupancy/Vacancy, Task Tuning, Energy Monitoring & Advanced Grouping control options. (Sensor not visible from exterior of fixture, max 12 ft mounting height)
 † † † † RF sensors provide: Wireless fixture control only. (Wireless controls must be located within 60 ft (18 m) from each other in the line of sight, or 30 ft (9 m) through walls)

PRIOR TO REPLACING AN EXISTING FLUORESCENT FIXTURE, PLEASE NOTE THE FOLLOWING:

Fluorescent lamps contain small amounts of mercury. Such lamps are labeled "Contains Mercury" and / or with the symbol "Hg." Lamps that contain mercury must be disposed of in accordance with local requirements. Information regarding lamp recycling and disposal can be found at www.lamprecycle.org.

SRW Cross Section & Fixture Dimensions



Note: Unless otherwise specified, all EKO's are 7/8" diameter.

CONSTRUCTION

- Precision die-formed from code-gauge cold rolled steel.
- Mechanically fastened (standard - when ordered as "PP" under "Housing Color / Finish" in the ordering guide).
- Resistance (spot) welded construction is optional.
- Consult factory for all options or any modifications needed.

FINISH

- Housing**
 - High Reflectance Gloss White polyester powder coat baked enamel. "PP" indicates White pre-paint (pop-riveted) construction. "GW" indicates Gloss White post paint (spot-welded) construction.
- Reflec or/Optics**
 - High Reflectance White polyester powder coat baked enamel for extreme durability and superior optical efficiency.

LENS (DIFFUSER)

- Frosted lens / diffuser manufactured from extruded, 100% virgin acrylic & high light transmission / LED diffusing polymer featuring linear ribbed pattern, which provides a clean, aesthetic architectural look.

DRIVERS

- Electronic, constant current type. Universal voltage (120v-277v).
- 0-10v dimmable. 10-100% (Standard)
 - o 100% (Optional).
- Line Voltage Dimming Drivers are optional.
- Auxiliary output (Optional) used to power various sensors / wireless modules. (12 or 24Vdc options specify when ordering)
- Suitable for dry and damp locations.
- UL Recognized Class P, RoHS Compliant.

LED's/OPTICS

- High performance LED boards manufactured specifically for interior lighting. LED boards feature the most current LEDs for maximum performance, efficiency and longevity.
- Standard color temperatures offered are 3500K and 4000K. Consult factory for all other color temperature options. 80 CRI (Minimum) standard, 90 CRI and Sunlike 95 CRI Options available.
- RoHS Compliant.
- Always consult factory for the latest developments and improvements concerning LEDs and Optics.

MOUNTING

- Fixtures are designed to be surface mounted, or suspended using pendant, aircraft cable, or jack chain. Consult factory for all other special mounting conditions.

ELECTRICAL

- Surface Mount Fixtures are UL/CUL listed and labeled for dry/damp locations.
- LM80 performance for 50,000+ hours
- Bi-Level dimming option allows 50% power for compliance with common energy codes.
- Driver disconnect provided where required to comply with US & Canadian codes.

QUALITY CONTROL

- All fixtures are designed, fabricated, assembled, tested, packaged and shipped from RENOVA's manufacturing facility in Warwick, RI (USA).

WARRANTY

- 5-year limited warranty. Please refer to RENOVA's website at www.renova.com/sales/warranties for the latest warranty terms and conditions.

NOTES:

LED Dimming Drivers have adjustable output capability. A wide range of input watts/lumen output can be adjusted up or down on all models to suit a particular application. Always consult factory for the latest information.


Photometric data, IES files and all other information is available on request.

RENOVA products are constantly being improved; therefore the information shown is subject to change without notice. Always consult your lighting representative or RENOVA Lighting Systems, Inc. for the latest information.




Catalog #: SRW4-N-L037-UNV-DM-C40-AF-XX-XX
Photometric Test Report #: 11201679-1231475
Delivered Lumens: 3738
Efficacy (Lumens/Watt): 137.8
Power: 27.13w @ 120 VAC
Power Factor: 0.996
Current THD: 5.72%
CRI: 83.7
CCT: 3988 K
LED Life: 50,000+ hrs

Candela Distribution Polar Plot



Spacing/Mounting Height: 1.22
SC (Along): 1.22 SC (Across): 1.22

Cone of Light Tabulation



Utilization of Lumens - Zonal Cavity Method
Effective Floor Cavity Reflectance 20%


Ceiling Cavity Reflectance	80				70				50		
Wall Reflectance	70	50	30	10	70	50	30	10	50	30	10
Room Cavity Ratio (RCR)	** Values are expressed as lumens delivered to the task surface **										
0	4428	4428	4428	4428	4315	4315	4315	4315	4103	4103	4103
1	4042	3863	3703	3558	3931	3769	3624	3491	3594	3474	3365
2	3687	3382	3130	2918	3580	3304	3073	2876	3157	2963	2796
3	3371	2984	2684	2445	3271	2918	2641	2417	2794	2558	2363
4	3095	2655	2333	2087	3003	2600	2300	2068	2495	2235	2030
5	2853	2382	2052	1809	2769	2335	2026	1795	2246	1975	1767
6	2640	2151	1823	1588	2563	2111	1802	1577	2035	1761	1556
7	2452	1956	1635	1409	2383	1922	1617	1401	1857	1584	1385
8	2286	1789	1477	1262	2223	1760	1463	1256	1703	1435	1243
9	2138	1646	1344	1140	2081	1620	1332	1135	1571	1308	1124
10	2007	1521	1230	1037	1955	1499	1220	1032	1456	1200	1024

Average Luminance (cd/m²)
Horizontal Angle (Degrees)

Angle	Along	45.0	Across
0	5604	5604	5604
45	4542	3953	3797
55	3869	3309	3257
65	3143	2711	2822
75	2349	2165	2446
85	1335	1608	2052

Horizontal Footcandles

Mounting Height = 8'-0" A.F.F.
Maximum Calculated Value = 18.43 Fc



Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	1093	29.2%
0-40	1752	46.9%
0-60	2918	78.1%
0-90	3648	97.6%
40-90	1896	50.8%
60-90	730	19.5%
90-180	90	2.4%
0-180	3738	100.0%

Luminaire Efficacy (Lumens Per Watt): 189.1

Grid Lines in Units of Mounting Height

5fc 2fc 1fc .5fc .2fc .1fc



SRW Fixtures Listed on the DLC Qualified Products List (QPL)

RENOVA Catalog Number	Delivered Lumens	Input Watts	Lumens per Watt	DLC – QPL Classification
SRW2-N-L015-UNV-DM-C35-AP-xx-xx	1469	11.62	126.41	Standard
SRW2-N-L015-UNV-DM-C35-AF-xx-xx	1464	11.47	127.63	Standard
SRW2-N-L015-UNV-DM-C40-AP-xx-xx	1488	11.77	126.42	Standard
SRW2-N-L015-UNV-DM-C40-AF-xx-xx	1483	11.77	125.99	Standard

RENOVA Catalog Number	Delivered Lumens	Input Watts	Lumens per Watt	DLC – QPL Classification
SRW4-N-L015-UNV-DM-C35-AP-xx-xx	1505	12.02	125.24	Standard
SRW4-N-L015-UNV-DM-C35-AF-xx-xx	1523	12.02	126.81	Standard
SRW4-N-L015-UNV-DM-C40-AP-xx-xx	1544	12.02	128.53	Standard
SRW4-N-L015-UNV-DM-C40-AF-xx-xx	1562	12.02	130.03	Standard

SRW4-N-L020-UNV-DM-C35-AP-xx-xx	2067	15.35	134.71	Standard
SRW4-N-L020-UNV-DM-C35-AF-xx-xx	2092	15.35	136.29	Standard
SRW4-N-L020-UNV-DM-C40-AP-xx-xx	2122	15.35	138.25	Standard
SRW4-N-L020-UNV-DM-C40-AF-xx-xx	2146	15.35	139.86	Standard

SRW4-N-L030-UNV-DM-C35-AP-xx-xx	3048	22.17	137.50	Standard
SRW4-N-L030-UNV-DM-C35-AF-xx-xx	3084	22.17	139.11	Standard
SRW4-N-L030-UNV-DM-C40-AP-xx-xx	3128	22.17	141.11	Standard
SRW4-N-L030-UNV-DM-C40-AF-xx-xx	3164	22.17	142.76	Standard

SRW4-N-L040-UNV-DM-C35-AP-xx-xx	3971	29.52	134.54	Standard
SRW4-N-L040-UNV-DM-C35-AF-xx-xx	4018	29.52	136.11	Standard
SRW4-N-L040-UNV-DM-C40-AP-xx-xx	4075	29.52	138.07	Standard
SRW4-N-L040-UNV-DM-C40-AF-xx-xx	4123	29.52	139.68	Standard

RENOVA Catalog Number	Delivered Lumens	Input Watts	Lumens per Watt	DLC – QPL Classification
SRW8-N-L030-UNV-DM-C35-AP-xx-xx	3235	21.98	147.19	Standard
SRW8-N-L030-UNV-DM-C35-AF-xx-xx	3273	21.98	148.91	Standard
SRW8-N-L030-UNV-DM-C40-AP-xx-xx	3320	21.98	151.05	Standard
SRW8-N-L030-UNV-DM-C40-AF-xx-xx	3358	21.98	152.82	Standard

SRW8-N-L040-UNV-DM-C35-AP-xx-xx	4235	29.03	145.90	Standard
SRW8-N-L040-UNV-DM-C35-AF-xx-xx	4285	29.03	147.61	Standard
SRW8-N-L040-UNV-DM-C40-AP-xx-xx	4346	29.03	149.73	Standard
SRW8-N-L040-UNV-DM-C40-AF-xx-xx	4397	29.03	151.48	Standard

SRW8-N-L060-UNV-DM-C35-AP-xx-xx	6195	43.66	141.91	Standard
SRW8-N-L060-UNV-DM-C35-AF-xx-xx	6268	43.66	143.56	Standard
SRW8-N-L060-UNV-DM-C40-AP-xx-xx	6358	43.66	145.63	Standard
SRW8-N-L060-UNV-DM-C40-AF-xx-xx	6432	43.66	147.33	Standard

SRW8-N-L080-UNV-DM-C35-AP-xx-xx	8029	59.00	136.09	Standard
SRW8-N-L080-UNV-DM-C35-AF-xx-xx	8123	59.00	137.68	Standard
SRW8-N-L080-UNV-DM-C40-AP-xx-xx	8239	59.00	139.66	Standard
SRW8-N-L080-UNV-DM-C40-AF-xx-xx	8336	59.00	141.29	Standard