



Series:  
Vapor Proof Series

Fixture Type :  
Large LED & Fluorescent Wall Mount Vapor Proof

Project Name	Fixture Type	Catalog #	Quantity
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>



VPW-L

### Design Features / Specifications

**HOUSING:**

Heavy Duty Die Cast Aluminum Housing & Screw On Guard, Chromate Conversion Coating, Repaintable Textured Gray Powdercoat Finish (Standard), 3/4" NPS Threaded Mounts. Includes Weatherproof Box with Coin Plugs.

**REFLECTOR:**

None

**LENS:**

Clear Glass Globe

**SOCKET:**

Compact Fluorescent: Plug-In Type, GX24Q-4

**LG LED Module:**

Luminous Flux: 800Lm @ 9w, 1300Lm @ 12w  
CRI: 70+, CCT: 4000K, 5700K or 6500K  
Operating Temperature: -40 ≈ 50°C  
50,000 Hours  
Module has IP67 Rating  
RoHS Compliant

**Compact Fluorescent Lamp:**

Luminous Flux: 1550Lm @ 26w,  
2050Lm@32w, 2750Lm @ 42w

**MOUNTING:**

Wall Mount

**WATTAGE:**



LED: 9w, 12w  
Compact Fluorescent: 26w, 32w, 42w

**LISTINGS & RATINGS:**

CSA: Listed for Wet Locations

Other Wattages & Custom Colors Available Upon Request.

### Dimensional Information Photometric Information



### Vapor Proof Series

Catalog # Description

**Complete Units**

**Ordering Information**

Example: VPW-L-F-1X26-UNV-50K-C-G-M-G

<b>VPW-L</b>	<b>Fixture Series:</b>	VPW-L = Vapor Proof (Wall Mount) - Large Style
	<b>Light Source:</b>	F = Compact Fluorescent L = Light Emitting Diode (LED)
<b>1X</b>	<b>Number of Lamps or LED Arrays:</b>	1X = One
	<b>Wattage:</b>	26 = 26w Compact (Fluorescent) 32 = 32w Compact (Fluorescent) 42 = 42w Compact (Fluorescent) 9 = 9w (LED) 12 = 12w (LED)
<b>UNV</b>	<b>Ballast (Fluorescent) or Driver (LED) Voltage</b>	UNV=Universal Voltage (120v-277v)
	<b>Color Temperature:</b>	27K = 2700K (Fluorescent) 30K = 3000K (Fluorescent) 35K = 3500K (Fluorescent) 41K = 4100K (Fluorescent) 40K = 4000K (LED) 57K = 5700K (LED) 65K = 6500K (LED)
<b>C</b>	<b>Lens Type</b>	C = Clear Glass Globe (Screw-On)
<b>G</b>	<b>Lens Guard Type</b>	G = Die Cast Aluminum Guard (Screw-On)
	<b>Lens Guard Color</b>	M = "Match Housing Color" W = White G = Gray (Standard) B = Black R = Red C = Custom (Specify)
	<b>Housing Color</b>	W = White G = Gray (Standard) B = Black R = Red C = Custom (Specify)
	<b>Options*</b>	(Blank) = None SF = Single Fuse

\* Contact Factory for all Other Options

Note: RENOVA products are constantly being improved; therefore, the information shown is subject to change without notice. Always consult your lighting representative or RENOVA Lighting Systems, Inc. for the latest information.