

Project Name	Fixture Type	Catalog #	Quantity
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>



Design Features / Specifications

ILLUMINATION

- Ultra-bright, energy efficient, long-life Red
- UV-stabilized ultra-clear acrylic edgelit panel provides consistent, uniform illumination.
- Double face utilizes factory installed LED silver or white mylar background panel.
- @V Kad 5fk Ua_ b TS f * : 7J ;F VVVVZ

ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long-life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Compatible with drywall or drop ceiling mount installations. Bar hangers included.

HOUSING

- Premium-grade, extruded aluminum housing.
- Extruded Aluminum trim assembly is easily detachable from below, providing accessibility for service or maintenance, also available in black or white powder-coated finishes.
- Self-adhesive Chevron appliques and guide template provided for directional indication.

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery pro rated for five years. Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes. UL Listed for wet locations (0°C – 50°C).

Electrical Information

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)	
	120v	277v	120v	277v
NYRELZXE-RED/EM/SPV	3.6	4.0	0.030	0.020

Note: RENOVA products are constantly being improved; therefore, the information shown is subject to change without notice. Always consult your lighting representative or RENOVA Lighting Systems, Inc. for the latest information.

NYC Approved Recessed Aluminum LED Edgelit Exit

Catalog # Description

Complete Units

Ordering Information

Example: NYRELZXE-1-R-M-W-EM

NYRELZXE	Model:	NYRELZXE = Recessed Aluminum LED Edgelit Exit
	# of Faces:	1 = Single Face 2 = Double Face
	Letter Color:	R = Red
	Panel:	C = Clear ¹ M = Mirror W = White
	Trim Plate:	W = White B = Black A = Aluminum
	Battery:	(Blank) = AC-Only EM = Battery Back-up
	Options:	SDT = Self-diagnostic ³ SPV = 208/220/240 Volt, 50/60Hz ² WM = Wall Mount ¹
Notes:	<ol style="list-style-type: none"> 1. Single face only 2. N/A with SDT option 3. EM Units only 	

Dimensional Information

