



Series: NYC Compliant Recessed LED Exit & Emergency Steel Combo (PRLEDCNYXTE) Fixture Type: Exit / Emergency Combo

Project Name	Fixture Type	Catalog #	Quantity
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>



NYC Compliant Recessed LED Exit & Emergency Steel Combo	
Catalog #	Description
Complete Units	
Ordering Information	
Example: PRLEDCNYXTE-3-R-W43	
<input type="text" value="PRLEDCNYXTE"/>	Model: PRLEDCNYXTE= Recessed LED Exit & Emergency Steel Combo
<input type="text"/>	# of Faces: 3 = Single Face
<input type="text"/>	Letter Color: R = Red
<input type="text"/>	Housing Color: W = White
<input type="text"/>	# of Heads: 43 = 3 Heads Standard

Design Features / Specifications

ILLUMINATION

- Ultra-bright, energy efficient, long-life Red
- Fully adjustable emergency lighting heads
- Knockouts provided on sides of unit to relocate lamp heads

ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- LVD (low voltage disconnect) prevents battery from deep discharge.
- 6V maintenance-free, rechargeable sealed lead acid battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Mounting hardware provided for back surface wall mount.
- Top and side knockouts provided for conduit feed applications.

HOUSING

- Durable, powder-coated 20-gauge steel construction
- Injection-molded, engineering grade, high impact, thermoplastic heads.
- Field removable steel knockouts chevron directional indicators on exit face.

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery pro rated for two years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

Electrical Information

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)	
	120v	277v	120v	277v
PRLEDCNYXTE	12.7	14.3	0.115	0.056

Note: RENOVA products are constantly being improved; therefore, the information shown is subject to change without notice. Always consult your lighting representative or RENOVA Lighting Systems, Inc. for the latest information.

Dimensional Information

