



Series:
Recessed Aluminum LED Edgelit Exit (ELXTEU)

Fixture Type:
Damp Location Exit Sign

Project Name	Fixture Type	Catalog #	Quantity
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>



Design Features / Specifications

ILLUMINATION

- Ultra bright, energy efficient, long life Red or Green LEDs.
- UV-stabilized ultra-clear acrylic edgelit panel provides consistent, uniform illumination.
- Double face utilizes factory installed silver or white mylar background panel.

ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long-life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge discharged battery in 24 hours.

MOUNTING

- Aluminum mounting canopy included for top, end or back mount.

HOUSING

- Premium-grade, extruded aluminum housing.
- Self-adhesive Chevron appliques and guide template provided for directional indication.

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery pro rated for five years. Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes. UL Listed for wet locations (0°C – 50°C). Certified to CEC under Title 20 Regulations.

Electrical Information

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)	
	120v	277v	120v	277v
ELXTEU-RED/EM/SPV	3.6	4.0	0.030	0.020

Note: RENOVA products are constantly being improved; therefore, the information shown is subject to change without notice. Always consult your lighting representative or RENOVA Lighting Systems, Inc. for the latest information.

Recessed Aluminum LED Edgelit Exit

Catalog # Description

Complete Units

Ordering Information

Example: ELXTEU-1-R-M-W-EM

ELXTEU	Model:	ELXTEU = Recessed Aluminum LED Edgelit Exit
	# of Faces:	1 = Single Face 2 = Double Face
	Letter Color:	R = Red G = Green
	Panel:	C = Clear ¹ M = Mirror W = White
	Trim Plate:	W = White B = Black A = Aluminum
	Battery:	(Blank) = AC-Only EM = Battery Back-up
	Options:	2C-120 = Dual Circuit With 120V Input ⁴ 2C-277 = Dual Circuit With 277V Input ⁴ SDT = Self-diagnostic ³ SPV = 208/220/240 Volt, 50/60Hz ²
	Notes:	1. Single face only 2. N/A with SDT option 3. EM Units only 4. Available only with AC units

Dimensional Information

