



Series:
Diecast Aluminum LED Exit Sign (KXTEU)

Fixture Type:
Damp Location Exit Sign

Project Name	Fixture Type	Catalog #	Quantity
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>



Design Features / Specifications

ILLUMINATION

- Ultra-bright, energy efficient, long-life Red

ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long-life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Aluminum mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

HOUSING

- Premium-grade, aluminum housing.
- Field selectable knockout Chevron directional indicators.
- Unique design allows double face conversion in the field.
- Quick-snap face plate closure.

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery pro rated for five years. Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes. UL Listed for wet locations (0°C – 50°C).
- Certified to CEC under Title 20 Regulations.

Electrical Information

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)	
	120v	277v	120v	277v
KXTEU/EM	5.0	5.0	0.041	0.018

Note: RENOVA products are constantly being improved; therefore, the information shown is subject to change without notice. Always consult your lighting representative or RENOVA Lighting Systems, Inc. for the latest information.

Diecast Aluminum LED Exit Sign

Catalog # Description

Complete Units

Ordering Information

Example: KXTEU-1-R-M-W-EM

<input type="text" value="KXTEU"/>	Model:	KXTEU = Diecast Aluminum LED Exit
<input type="text"/>	# of Faces:	1 = Single Face 2 = Double Face 3 = Universal Single/Double Face
<input type="text"/>	Letter Color:	R = Red
<input type="text"/>	Housing Color:	W = White M = Mirror A = Aluminum
<input type="text"/>	Trim Plate:	W = White B = Black A = Aluminum
<input type="text"/>	Battery:	(Blank) = AC-Only EM = Battery Back-up
<input type="text"/>	Options:	SDT = Self-diagnostic ² 2C = Dual Circuit Operation ¹
Notes:		1. AC Units only 2. EM Units only

Dimensional Information

