¥)	Series: NYC Compliant Recessed	Fixture Type : Damp Location Exit Sign		
RENOVA	Project Name	Fixture Type	Catalog #	Quantity



Design Features / Specifications

ILLUMINATION

- Ultra bright, energy efficient, long life Red LEDs.
- UV-stabilized ultra-clear acrylic edgelit panel provides consistent, uniform illumination.
- Double face utilizes factory installed silver or white mylar background panel.
- New York City compliant 8" EXIT letters

ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long-life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

• Aluminum mounting canopy included for top, end or back mount.

HOUSING

- Premium-grade, extruded aluminum housing.
- Self-adhesive Chevron appliques and guide template provided for directional indication.

WARRANTY / LISTING

 Five year warranty on all electronics and housing. Battery pro rated for five years. Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes. UL Listed for wet locations (0°C – 50°C). Certified to CEC under Title 20 Regulations.


Electrical Information

	INPUT WATTS (W) INPUT AMPS		MPS (A)	
CATALOG NUMBER	120v	277v	120v	277v
NYELXTEU-RED/EM/SPV	3.6	4.0	0.030	0.020

Note: RENOVA products are constantly being improved; therefore, the information shown is subject to change without notice. Always consult your lighting representative or RENOVA Lighting Systems, Inc. for the latest information.

Catalog #	Description				
Complete Units Ordering Information Example: NYELXTEU-1-R-M-W-EM					
NYELXTEU	Model:	NYELXTEU = Recessed Aluminum LED Edgelit Exit			
	# of Faces:	1 = Single Face 2 = Double Face			
	Letter Color:	R = Red			
	Panel:	$C = Clear^{1}$ M = Mirror W = White			
	Trim Plate:	W = White B = Black A = Aluminum			
	Battery:	(Blank) = AC-Only EM = Battery Back-up			
	Options:	SDT = Self-diagnostic ³ SPV = 208/220/240 Volt, 50/60Hz ²			
Notes:	 Single face only N/A with SDT option EM Units only 				

Dimensional Information



RENOVA Lighting Systems, Inc. • 36 Bellair Avenue, Warwick, RI 02886 • (800) 635-6682 • www.renova.com