



Series:  
**NYC Compliant Steel LED Exit Sign (NYXTEU)**

Fixture Type:  
**Steel Exit Sign**

Project Name	Fixture Type	Catalog #	Quantity
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>



### NYC Compliant Diecast Steel LED Exit Sign

Catalog #    Description

**Complete Units**

**Ordering Information**

Example: NYXTEU-1-R-M-W-EM

<input type="text" value="NYXTEU"/>	<b>Model:</b>	NYXTEU = Steel LED Exit
<input type="text"/>	<b># of Faces:</b>	1 = Single Face 2 = Double Face 3 = Universal Single/Double Face
<input type="text"/>	<b>Letter Color:</b>	R = Red
<input type="text"/>	<b>Housing Color:</b>	W = White B = Black
<input type="text"/>	<b>Battery:</b>	(Blank) = AC-Only EM = Battery Back-up
<b>Notes:</b>		1. AC Units only 2. EM Units only

### Design Features / Specifications

**ILLUMINATION**

- Ultra-bright, energy efficient, long-life Red LED
- New York Compliant 8" Exit letters

**ELECTRICAL**

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 3.6V long-life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

**MOUNTING**

- Aluminum mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.
- Top and side K/O provided for conduit feed applications.

**HOUSING**

- Durable, powder-coated 20-gauge steel construction in white or black finish.
- Field removable steel knockout Chevron directional indicators.
- Unique design allows double face conversion in the field.

**WARRANTY / LISTING**

- Five year warranty on all electronics and housing. Battery pro rated for five years. Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes. UL Listed for wet locations (0°C – 50°C).
- Certified to CEC under Title 20 Regulations.

### Electrical Information

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)	
	120v	277v	120v	277v
<b>NYXTEU/EM</b>	5.0	5.0	0.041	0.018

*Note: RENOVA products are constantly being improved; therefore, the information shown is subject to change without notice. Always consult your lighting representative or RENOVA Lighting Systems, Inc. for the latest information.*

### Dimensional Information

