

Steel Exit Sign (SXTEU)

Fixture Type:

Damp Location Exit Sign

Project Name	Fixture Type	Catalog #	Quantity



Design Features / Specifications

ILLUMINATION

· Ultra-bright, energy efficient, long-life Red / Green LEDS

ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long-life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

HOUSING

- Durable, powder-coated 20-gauge steel construction in white or finish.
- Unique design allows double face conversion in the field.
- Field selectable steel knockout Chevron directional indicators.

WARRANTY / LISTING

Five year warranty on all electronics and housing. Battery pro rated for five years.
 Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
 UL Listed for wet locations (0°C – 50°C).

Electrical Information

	INPUT WATTS (W) INPUT AM		MPS (A)	
CATALOG NUMBER	120v	277v	120v	277v
SXTEU-RED/Green/EM/SDT	3.8	3.8	0.034	0.020

Note: RENOVA products are constantly being improved; therefore, the information shown is subject to change without notice. Always consult your lighting representative or RENOVA Lighting Systems, Inc. for the latest information.

Steel Exit Catalog #				
Complete Units Ordering Information Example: SXTEU-2-R-W-EM				
SXTEU	Model:	SXTEU = Steel Exit Sign		
	# of Faces:	2 = Universal Single/Double Face		
	Letter Color:	R = Red G = Green		
	Housing:	W= White B = Black		
	Battery:	(Blank) = AC-Only EM = Battery Back-up		
	Options:	SDT = Self-diagnostic ¹		
Notes:	1. EM Units o	only		

Dimensional Information

