

## 10", 14" & 18" Round Ceiling Luminaires

Prefix: LEDR

The LED round (LEDR) ceiling series is designed for residential, light commercial and other applications. High-quality luminaire utilizes the latest LED technology for optimal performance and maximized energy efficiency. High-CRI LEDs are standard, and dimming is available with many popular wall dimmers. The finely-textured lens is molded from acrylic, and provides an even, uniform light distribution.



10", 14" & 18" Round Ceiling Luminaires



project:

fixture type:

catalog #:

quantity:

### ORDERING GUIDE

	-	<b>KFS</b>	-	
<b>MODEL</b>		<b>COLOR TEMPERATURE</b>		<b>COMPATIBLE DIMMERS</b>
<b>LEDR11-L010</b> 10" Round, 1000lms (15w) <b>LEDR14-L018</b> 14" Round 1800lms (20w) <b>LEDR18-L020</b> 18" Round 2000lms (20w)		<b>KFS</b> - Field Selectable 2700K 3000K 3500K 4000K 5000K		<b>LUTRON</b> <b>Diva</b> -DVCL-153PR-WH <b>Diva</b> -CTCL-153PDH-WH <b>Diva</b> -TGCL-153PH-WH <b>Diva</b> -MACL-153MH-WH <b>Diva</b> - P-PKG1W-WH-R  <b>LEVITON</b> R62-06674-P0W R12-06672-1LW R50-IPL06-10M

### FEATURES

- Field selectable 2700k (soft white), 3000k (warm white), 3500k (warm/neutral white), 4000k (neutral white), and 5000k (cool white) color temperatures.\*
- Long-life LEDs provide at least 70% of initial lumen output (L70) for 93,000 hours of operation.\*\*
- Color rendering index (Ra) > 90.
- Input voltage = 120V 60Hz.
- Power factor > 0.90.
- Triac dimming.
- Steel housing, brushed nickel finish.
- Polystyrene lens.
- Easy installation in new construction or remodel applications.
- This device is not intended for use with emergency exits.

### WARRANTY & LISTINGS

- cETLus listed for damp locations in ambient temperatures of -15°C to 40°C (5°F to 104°F).
- Energy Star qualified.
- Title 24 qualified.
- Complies with FCC Part 15, class B.
- Input transient protection = 1kV.
- 5-year warranty of all electronics and housing.

## Dimensions

